

Package: kissatire (via r-universe)

May 27, 2026

Type Package

Title SAT Solver using 'Kissat'

Version 1.0.0.9000

Maintainer Mike Cheng <mikefc@coolbutuseless.com>

URL <https://github.com/coolbutuseless/kissatire>

BugReports <https://github.com/coolbutuseless/kissatire/issues>

Description A solver for Boolean satisfiability problems ('SAT') using the 'Kissat' library. For this solver, 'SAT' problems can be formulated in two ways; using integer literals, or using logical expressions specified with the 'satire' package.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

Imports satire (>= 1.0.0.9000)

Suggests knitr, rmarkdown, testthat (>= 3.0.0), glue, ggplot2, purrr

Config/testthat/edition 3

Copyright The included 'Kissat' code is Copyright (c) Armin Biere. See 'COPYRIGHTS' file for LICENSE for included code.

Remotes coolbutuseless/satire

VignetteBuilder knitr

OS_type unix

Config/pak/sysreqs libicu-dev

Repository <https://coolbutuseless.r-universe.dev>

Date/Publication 2025-04-07 01:05:11 UTC

RemoteUrl <https://github.com/coolbutuseless/kissatire>

RemoteRef HEAD

RemoteSha 6fa120e06a97d5224aafb9441129749ac24b13af

Contents

kis_solve_literals	2
kis_solve_satire	2
kis_version	3

Index	4
--------------	----------

kis_solve_literals	<i>Solve using literals</i>
--------------------	-----------------------------

Description

Solve using literals

Usage

```
kis_solve_literals(literals, max_solutions = 1)
```

Arguments

literals	integer literals
max_solutions	limit number of solutions

Value

Return NULL if problem is unsatisfiable. Otherwise return a list of integer sequences of literals - each sequence is a solution.

Examples

```
kis_solve_literals(c(1, 2, 0, 2, -3, 0))
```

kis_solve_satire	<i>Solve using 'satire'</i>
------------------	-----------------------------

Description

Solve using 'satire'

Usage

```
kis_solve_satire(sat, max_solutions = 1, remove = "^dummy")
```

Arguments

sat	SAT problem definition as created by <code>satire::sat_new()</code> or <code>satire::read_dimacs()</code>
max_solutions	limit number of solutions
remove	regular expression for variables to remove when blocking solutions and assembling values to return. Default: " <code>^dummy</code> " will block all variables starting with the word "dummy" (as this is how the 'satire' package automatically creates dummy variables.) If NULL no variables will be removed.

Value

Return NULL if problem is unsatisfiable. Otherwise return a data.frame of solutions where each column represents a named variable in the problem and each row is a solution.

Examples

```
sat <- satire::sat_new()
satire::sat_add_exprs(sat, "a -> (b & c)")
kis_solve_satire(sat, max_solutions = 10)
satire::sat_solve_naive(sat)
satire::sat_solve_dpll(sat, max_solutions = 10)
```

 kis_version

Return a list of version information of the kisSAT library

Description

Return a list of version information of the kisSAT library

Usage

```
kis_version()
```

Value

Named list of version information. `kisSAT_API_VERSION` is the internal C API version, and `release` is the numbering of the software release tarball.

Examples

```
kis_version()
```

Index

`kis_solve_literals`, [2](#)
`kis_solve_satire`, [2](#)
`kis_version`, [3](#)